



## Fragrance dosing systems for the dosing of several aromas

### 13163-1-DUFTDOS VARIO W-4-UNPL-COMPACT

#### FUNCTION DESCRIPTION

Dosing system for the dosing of several fragrances into the steam pipe of steam rooms. The desired aroma is chosen by a pre-selector switch at the controller of the unit by the operator. After the setting of the aroma it is dosed in adjustable intervals. The dosing performance is adjusted by the pause time and the dosing time by rotary knobs at the housing. Operation only when steam is produced.



#### SCOPE OF DELIVERY

- 4 x Peristaltic pump SA app. 3 l/h with dosing hoses 3.2 x 1.6 V with hose holder 4 x 1 and suction hose (PE 0.8 m)
- Controller UNPL for pause- and dosing time
- 4 x Bottle à 1.5 l
- Console with the components pre-installed
- 4 x dosing valve stainless steel 3/8" - 4 x 1
- 4 x 3 m dosing tube PTFE 4 x 1

#### TECHNICAL DATA

Electrical supply	230 V/AC 50 Hz
Power supply	6 W
Back pressure max.	app. 0.5 bar
Measures	W 600 mm x H 500 mm x D 200 mm
Weight	app. 5 kg

#### ACCESSORIES / OPTIONS

- Available also for 2 or 3 aromas (on demand)