



FOG SHOWER W2 WITH CEILING ELEMENT PVC

FUNCTION DESCRIPTION

After the start of the programme by a button, the light in the shower changes from white to blue. A cold, refreshing Fog with very fine droplets starts to spray and a minty, cooling aroma fills the air. In a distance you hear the sound of waves and sea. After the end of the programme, the illumination changes back to white, the Fog and the sound are switching off. The endurance of the programme and the aroma intensity can be adjusted individually at the controller. As an option, the tubing to the nozzles can be emptied automatically after the programme.

SCOPE OF DELIVERY OF A COMPLETE PACKAGE

CONTROL PANEL



Control panel incl. listed parts, pre-tubed, pre-wired and pre-mounted on PP board grey - Part no. 13428:

- Supply with pre-filter and ball valve MS ½" female thread
- Outlet with solenoid valve ½" and screwing ½"
- Fragrance pump with fragrance reservoir and empty switch
- Dosing valve for the injection of aroma into the water tube
- Microprocessor controller EDS1 in housing

TECHNICAL DATA

Electrical supply	230 V-AC, 50 Hz
Power supply	100 W
Water supply	½" female thread
Dimensions (W/H/D)	500 x 650 x 200 mm
Weight	app. 10 kg

PUSH BUTTON

Details see page 72



- 1 x Push-button plate 1-fold Alu-Dibond - Part no. 19011
- 1 x Bonnet 1-fold - Part no. 21030-1
- 1 x Name plate "Cold Mist" - Part no. 19951

CEILING ELEMENT INCL. ILLUMINATION

Details see page 76



1 x Ceiling element PVC white Ø 800 x 19 mm with 3 LED Spots RGB Ø 48 incl. RGB controller SAU and 7 m cable with 2 connections for 2 nozzles - Part no. 21748-1

NOZZLES

Details see page 74

- 2 x Fog Nozzle ½" - Part no. 13526
- 2 x Cover Screen for Fog Nozzle - Part no. 13877

SOUND

Details see page 80



- 1 x Sound module MP3 - Part no. 18824-1
- 1 x Speaker - Part no. 14366-4

TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Power supply
- Water connection cold ½"
- Needed pressure: 3 bar dynamic
- Water quantity: app. 10 l/min at the use of 2 Fog Nozzles
- Tubing to the nozzles
- Non-return according to DIN EN 1717 in the supply
- Drain in the plants room

ACCESSORIES / OPTIONS

- Optionally you can use Corian® or backlit ceiling element instead of PVC
- Fragrance
- Emptying